

Fixed Point Algorithm based on Proximity and Precondition Operator for High-Resolution Image Reconstruction with Displacement-Errors

Wenting Long¹ & Lixin Shen² & Yuesheng Xu^{1,2}

¹Sun Yat-sen University, Guangzhou, China

²Syracuse University, NY, USA

School of Mathematics and Computational Science

Sun Yat-sen University

Guangzhou, Guangdong, China

Phone: +86 185 2038 3927

Email: longwenting@gmail.com



中山大學
SUN YAT-SEN UNIVERSITY

Introduction

High resolution image reconstruction arises in many applications, such as remote sensing, surveillance, and medical imaging. It refers to the reconstruction of high-resolution image from multiple low-resolution, shifted, degraded samples of a true image. In this work we consider Bose-Boo observation model to reconstruct HR image. Displacement error is inevitable during the capture of low resolution images. The goal for this work is to address the specific issue of high resolution image reconstruction with displacement error by proposing a novel optimization model invoking the Moreau envelop, denoted by $\text{env}_{\ell^1}/\text{TV}$, which has been studied and explored extensively in the present work, to compensate the bad performance of L_2/TV deblurring model while dealing with realistic noisy data and a fixed point algorithm with precondition is proposed, whose convergence condition has been given in the meantime, and an adaptive strategy has been given for better PSNR appearance and faster convergence rate. Numerical results shows the method of $\text{env}_{\ell^1}/\text{TV}$ model combine new algorithm has very fast convergent speed in dealing with both Gaussian noise and salt & pepper noise.

Bose-Boo Observation Model[2]




Figure 1: Bose-Boo model for amplifying four times. (a) shows where LR sensors will be placed, while (b) shows the composite matrices of LR images and high resolution image.

The relationship of HR image and LR images can be formed as

$$\vec{C} = A_L(\varepsilon^x, \varepsilon^y) \vec{U} + \eta$$

where

$$A_L(\varepsilon^x, \varepsilon^y) = \frac{1}{L \times L} \sum_{p,q=1}^L D_{p,q} A_L(\varepsilon_{p,q}^x, \varepsilon_{p,q}^y),$$

in which

$$D_{p,q} := J_q \otimes J_p, \quad A_L(\varepsilon_{p,q}^x, \varepsilon_{p,q}^y) := A_L(\varepsilon_{p,q}^x) \otimes A_L(\varepsilon_{p,q}^y),$$

$$A_L(\varepsilon) = \frac{1}{L} \text{Toeplitz}(a, b) + \frac{1}{L} \text{Hankel}(c, d)$$

where

$$a = \underbrace{[1, \dots, 1]_{\frac{1}{2}}}_{\frac{1}{2}} + \varepsilon, 0, \dots, 0, \quad b = \underbrace{[1, \dots, 1]_{\frac{1}{2}}}_{\frac{1}{2}} - \varepsilon, 0, \dots, 0,$$

$$c = \underbrace{[1, \dots, 1]_{\frac{1}{2}-1}}_{\frac{1}{2}-1} + \varepsilon, 0, \dots, 0, \quad d = \underbrace{[1, \dots, 1]_{\frac{1}{2}-1}}_{\frac{1}{2}-1} - \varepsilon, 0, \dots, 0,$$

η denotes the additive noise.

Optimization Model




Figure 2: Displacement error. (a) Original image, (b) random displacement error with $\varepsilon_{\max} = 0.99$.

Definition 0.1. Let $f : \mathcal{H} \rightarrow (-\infty, +\infty]$ and let $\tau \in \mathbb{R}_{++}$. The Moreau envelop [2] of f respects to parameter τ is

$$\text{env}_{\tau} f(x) = \min_{y \in \mathcal{H}} \{f(y) + \frac{1}{2\tau} \|x - y\|_2^2\}. \quad (1)$$

Proposition 0.2. The moreau envelope of f satisfies that $\text{env}_{\tau} f(x)$ is continuous differentiable and the gradient of it is

$$\nabla \text{env}_{\tau} f(x) = \frac{1}{\tau} (I - \text{prox}_{\tau f}(x)).$$

We can prove that $\text{env}_{\tau} \|\cdot\|_1(x)$ has β -Lipschitz continuous gradient. Combine all these analyses, we propose a modified model (2):

$$u^* = \arg \min_{u \in \mathbb{R}^n} \{\mu \|u\|_{\text{TV}} + \text{env}_{\tau} \|\cdot\|_1(Au - c), c \in \mathbb{R}^n\}. \quad (2)$$




Figure 3: $\mathbb{R}^1$ situation. (a) The figures of L1 norm, L2 nom and Moreau envelop. (b) The figures of influence functions of L1 norm, L2 nom and Moreau envelop.

FP³ Algorithm

For optimization model

$$u^* = \arg \min_{u \in \mathcal{H}} \{p_1(Bu) + p_2(Au), u \in \mathbb{R}^n\} \quad (3)$$

where $p_1, p_2 \in s_0(\mathbb{R}^n)$, and $p_2(A \cdot)$ is differentiable with a β -Lipschitz continuous gradient. We have the following theorem:

Theorem 0.3. Let $p_1 \in s_0(\mathbb{R}^m)$, $p_2 \in s_0(\mathbb{R}^n)$, $\lambda > 0$, $A \in \mathbb{R}^{m_1 \times n}$, $B \in \mathbb{R}^{m_2 \times n}$. If u is a solution of model (2), as function p_2 is differentiable, then for any $\lambda > 0$ and $S \in \mathbb{S}_+^n$, there exists a vector $v \in \mathbb{R}^{m_2}$,

such that the pair $(v, u) \in \mathbb{R}^{m_2} \times \mathbb{R}^n$ satisfies the following coupled fixed point equations:

$$v = (I - \text{Prox}_{\lambda p_1})(v + Bu) \quad (4)$$

$$u = u - S(A^T \nabla p_2(Au) + \frac{1}{\lambda} B^T v). \quad (5)$$

Conversely if $u \in \mathbb{R}^n$ satisfies equations (4)-(5) for some $\lambda > 0$ and $S \in \mathbb{S}_+^n$, then it is a solution of model (3).

Algorithm 1. Fixed point algorithm based on proximity and precondition operator, FP³.

Step 1: set S being a symmetric positive definite matrix and $\|S\|_2^2 < \frac{1}{2\beta}$.

Step 2: for $k = 0, 1, 2, \dots$,

$$v_{k+1} = (I - \text{Prox}_{\lambda p_1})(Bu_k + v_k),$$

$$u_{k+1} = u_k - S(A^T \nabla p_2(Au_k) + \frac{1}{\lambda} B^T (2v_{k+1} - v_k)).$$

end for

Algorithm 2. Fixed point algorithm based on proximity operator accelerated by adaptive parameters

Step 1: Set $u_0 \in \mathbb{R}^n$, $v_0 \in \mathbb{R}^m$, Adaptive Frequency, S being a symmetric positive definite matrix and $\|S\|_2^2 < \frac{1}{2\beta}$,

Step 2: For $k = 0, 1, 2, \dots$

$$z = \text{rem}(m1, \text{Adaptive Frequency});$$

$$\text{if } z == 0 \quad i = i + 1; \quad \text{else} \quad \text{end}$$

$$\tau = 128/2^i; \quad s = \tau;$$

$$v_{k+1} = (I - \text{Prox}_{\lambda p_1})(Bu_k + v_k),$$

$$u_{k+1} = u_k - S(A^T \nabla p_2(Au_k) + \frac{1}{\lambda} B^T (2v_{k+1} - v_k)).$$

end for.




Figure 4: The PSNR of reconstructed images with different paramete τ and s . (a) are the reconstruction results of ‘electricpad’, (b) are the reconstruction results of ‘phantom’.

Numerical Results

	$\lambda = 1$	$\lambda = 2$	$\lambda = 4$	$\lambda = 8$	$\lambda = 16$
TOL = 10^{-3} $\delta^2 = 10^{-3}$	L ₂ /TV 32.4717(40)	32.5323(3)	32.5888(3)	32.6400(3)	32.7007(4)
	env _{ℓ¹} /TV 32.5149(70)	32.5167(70)	32.5582(61)	32.5629(61)	32.6356(52)
E ₁ = 10^{-3}	L ₂ /TV 32.6833(40)	32.7272(2)	32.7743(2)	32.8232(2)	32.8719(2)
	env _{ℓ¹} /TV 34.7588(70)	34.7594(70)	34.6546(61)	34.6483(61)	34.5120(52)
TOL = 10^{-4} $\delta^2 = 10^{-3}$	L ₂ /TV 32.8640(100)	32.8666(87)	32.9078(31)	32.9405(41)	32.8904(55)
	env _{ℓ¹} /TV 32.4752(91)	32.4841(82)	32.4835(80)	32.4926(80)	32.5133(80)
E ₁ = 10^{-3}	L ₂ /TV 33.1906(100)	33.2609(76)	33.3610(28)	33.5251(35)	33.7351(46)
	env _{ℓ¹} /TV 34.8514(91)	34.8317(87)	34.8250(86)	34.8472(86)	34.8778(86)

Table 1: PSNR(dB) results of reconstructed image ‘lena’ with different λ under different stopping criterion.

